


# HIGHBAY LIGHT

SPGK015-SERIES



#### **Aviation Aluminum LED High Bay**













SPGK015 series LED High Bay Light has high-quality aviation aluminum( 1060 Al metal sheet) for heat sink,UFO appearance design, light weight structure, beautiful and stylish, high temperature, corrosion resistance, suitable for a variety of harsh working environments..

Optional function: microwave induction and DALI / 0-10V / PWM optional dimming features.It is an excellent product for industrial and mining, factories, warehouses, stadiums, exhibition halls and other large space.














Microwave sensor
Detailed reference manual

10,0000 Hours

### **Explosive View**



High quality polycarbonate shatter proof diffuser provides assurances

and safety in the work places with low UGR value.

**LENS** 

### **Feature**

### High efficacy as always, up to 170lm/W

LED chip from US with high luminous efficiency, luminaire efficacy up to 170 lm / W, 40% energy saving than conventional LED high bay light, significantly reducing energy costs.

#### No Glare

Design of professional light distribution, effectively prevent glare, and provide better visual comfort.

#### Smart as always

0-10V / DALI / PWM intelligent dimming control optional, intelligent control brightness, less costs with much more energy-saving.

### Optional microwave induction

The function of microwave induction is optional, which can make people switch off the lamp and reduce energy cost greatly..

### Fashion shape design

UFO appearance design, lightweight structure, beautiful fashion, leading industrial lighting.

### **Application**

Mining, factories, warehouses, stadiums, exhibition halls, workshops and other large high-altitude lighting case.









# **Specifications**

Model No.	SPGK015-100	SPGK015-150	SPGK015-200
Rated Power	100W	150W	200W
Luminous Flux(Im)	13000/15000/17500	19500/22500/25500	26000/30000/34000
Luminous Efficiency (lm/W)	130/150/170 lm/W		
Beam Angle	60°/90°/120°		
CCT	5000K/5700K/6500K		
Power Factor	0.95		
Input Voltage	100-277VAC 50/60Hz		
Storage Voltage	-40°C ~ +80°C		
Working Temperature	-40°C ~ +50°C 10% ~ 90RH		
IP Rating	IP66		
N.W	2.08kg	2.95kg	2.95kg
G.W	3.25kg	4.15kg	4.15kg
Product Size	Ф260×170mm	Ф302×183mm	Ф302×183mm
Packing size	302X302X210mm	342X342X220mm	342X342X220mm
Installation Method	Hanging install/ Bracket install		


## Outline Drawing (Unit:mm)





# **Photometric Diagrams**



### Installation









## **Packing**

### 1. Packaging Sketch Map



### 2. Product Labeling





#### 3. Mark Label



#### **Shenzhen Spark Optoelectronics S&T Co., Ltd.**

#### Headquarter

27th floor,Block A,Shenzhen International Innovation Center,1006 Shennan Rd.,Shenzhen,China

ZIP:518035

Tel: +86-755 8308 8855 +86-755 8390 4366 Fax: +86-755 8391 4431 +86-755 8390 4766

24-Hour Service Hotline: 400-6232311

E-mail: spark@spark-oe.com Web: www.sparkoe.com

#### **Factory**

Wanlida Industrial Park, Fuyuan 1st Road, Heping Village, Fuyong

Town, Baoan District, Shenzhen, China

ZIP: 518103

Tel: +86-755 2959 6112 Fax: +86-755 2959 6117